



1



2



3



4



5

STANDARD EQUIPMENT:

- 3-point linkage - cat.II (adjusted to be moved by pallet forks)
- Sheet thickness: side walls- 5-6 mm; bottom- 8 mm
- Mixer arms made from 3 flat springs, 4 arms (600 l and 800l) or 5 arms (1200 l), rotating around 30 rpm.
- Ew of stirrers to padles with working height adjustment
- Mesh for segregation during the filling
- Rear and side unloading for 800l and 1200l, rear unloading for 600l
- Protective metal screen on the tractor side
- In standard option PTO drive. Power required 600 l – 60 HP, 800 l – 80 HP, 1200 l – 110 HP

OPTIONAL EQUIPMENT:

- Hydraulic drive. Recommended oil flow for mixer 600 l and 800 l – 70-90 l/min., 1200 l – 100-130 l/min.
- Electric drive (360 V)
- PTO shaft version + hydraulic drive (standard PTO drive mixer is ready to install hydraulic drive)

- Self loading bucket
- Rotary rear unloading
- Hardox reinforced paddles
- PTO shaft 460 Nm with overload protection

Ref. No.	Capacity /l/	Tank diameter /Ømm/	High/ Transport high /mm/	Type of drive	Weight /kg/
2430	600	1200	1330/1220	PTO	450
2431	800	1500	1330/1220	PTO	550
2432	1200	1900	1330/1220	PTO	750
2430H	600	1200	1330/1220	hydr.	450
2431H	800	1500	1330/1220	hydr.	550
2432H	1200	1900	1330/1220	hydr.	750
2430E	600	1200	2062/1952	elektr.	650
2431E	800	1500	2062/1952	elektr.	750
2432E	1200	1900	2062/1952	elektr.	950

self-loading bucket

Ref. No.	Volume /l/	Weight /kg/
600S	250	180
800S	330	200
1200S	440	220